

## FE02.3... INLET MODULE UNITS

WITH PRESSURE RELIEF VALVE (UP TO 15 l/min)



FE02.3...

Module units FE10.3... provide pressure relief valve with adjustable pressure setting ranges.

Manual adjustment is available by a grub screw or plastic knob. Maximum flow is 15 l/min.

The threaded ports (P and T) are available in two different sizes: G3/8" or 9/16-18UNF.

Max. operating pressure	250 bar
Setting ranges:	spring 1 30 bar
	spring 2 90 bar
	spring 3 180 bar
	spring 4 250 bar
Max. flow	15 l/min
Hydraulic fluids	Mineral oils DIN 51524
Fluid viscosity	10 ÷ 500 mm <sup>2</sup> /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Max. contamination level	class 10 in accordance with NAS 1638 with filter $\beta_{25} \geq 75$
Weight	0,6 Kg

### ORDERING CODE

**FE02**

Inlet module unit (up to 15 l/min) with pressure relief valve

**3**

Size

\*

Port sizes:

**1** = G3/8"

**2** = 9/16-18UNF

**C**

Adjustment:  
Grub screw

\*

Setting ranges

**1** = max. 30 bar (**white spring**)

**2** = max. 90 bar (**yellow spring**)

**3** = max. 180 bar (**green spring**)

**4** = max. 250 bar (**orange spring**)

\*\*


**00** = No variant

**V1** = Viton


**1**

Serial No.

### PRESSURE - FLOW RATE



### MINIMUM SETTING PRESSURE



### OVERALL DIMENSIONS AND HYDRAULIC SYMBOL

